

Welded Bellows



Type	OD	ID	Thickness
D055S	5.5	3	0.05
D0100S	10	5	0.05
D0150S	15	6.5	0.05
D0170S	17	8	0.1
D0200S	20	11	0.05
D0250S	25	16	0.08
D0276S1	27.6	20	0.05
D0400S1	40	30	0.05
D0300B	30	19	0.1
D0222A	22	9.17	0.1
D0280A	28	15.2	0.1
D0320A	32	19.2	0.15
D0341A	34.1	21.3	0.15
D0353A	35.3	22.5	0.1
D0381A	38.1	25.3	0.1
D0460A	46	33.5	0.1
D0478A	47.8	35	0.1
D0495A	49.5	36.7	0.1
D0524A	52.4	39.6	0.1
D0540A	54	41.2	0.1
D0597A	59.7	46.9	0.1
D0650A	65	52.2	0.1
D0395A	39.5	25.9	0.1
D0370E	37	23	0.1
D0442E	44.2	30	0.1
D0250T	25	10	0.1
D0270T	27	12	0.1
D0500T	50.0	35.0	0.1
D0820T	82.0	67.0	0.1
D0920T	92.0	76.0	0.1
D0710G	71.0	54.0	0.1
D0500G	50.0	33.0	0.1
D0400G	40.0	22.0	0.1
D0341H	34.1	14.9	0.1

D0412H	41.2	22.0	0.1
D0445H	44.5	25.3	0.1
D0460H	46.0	26.8	0.1
D0510H	51.0	31.8	0.1
D0562H	56.2	37.0	0.1
D0600H	60.0	40.0	0.1
D0650H	65.0	45.8	0.1
D0692H	69.2	50.0	0.1
D0750H	75.0	55.8	0.1
D0770H	77.0	57.5	0.1
D0800H	80.0	60.8	0.1
D1292H	129.2	110.0	0.1
D0395L	39.5	19.0	0.1
D0365L2	36.5	16.5	0.1
D0587L2	58.7	38.7	0.1
D1690L2	169.0	149.0	0.2
D0885KR3	88.5	65.5	0.1
D0885KR4	88.5	65.5	0.1
D0950K	95.0	72.0	0.1
D0445D	44.5	18.9	0.1
D0495D	49.5	23.9	0.1
D0570D2	57.0	32.0	0.1
D1080U	108.0	80.0	0.1
D1300U	130.0	102.0	0.1
D1660U	166	138	0.15
D0395V2	39.5	10	0.1
D0700V	70	40	0.13
D1000V	100	70	0.1
D1070V	107	77	0.12
D1200V	120	90	0.1
D1500V	150	120	0.15
D2000V	200	170	0.15
D2350X	235	200	0.1
D1370X2	137	102.9	0.13
D1300W	130	90	0.13
D1450W	145	105	0.13
D1600W	160	120	0.15
D1900W	190	150	0.15
D2100W	210	170	0.15

D1850P	185	135	0.15
D5100P	510	426	0.2
Set up new mold according to customer's requirement.			